

## Three Easy Steps. One Lifetime Warranty.

Tres pasos sencillos. Una garantía de por vida.



Custom's Lifetime Warranty guarantees that your installation products will be free from manufacturing defects and will not break down or deteriorate under normal usage. If a defect occurs, Custom will cover the cost of materials and labor to repair.

La garantía de por vida de Custom garantiza que los productos de su instalación estarán libres de defectos de fabricación que no se agreden o deterioran bajo condiciones de uso normal. En caso de producirse un defecto, Custom cubrirá el costo de los materiales y el costo de mano de obra para efectuar la reparación.

### 1 Prep Preparar

Determine products needed to prepare your surface.  
Determinar los productos necesarios para preparar la superficie.

### 2 Set Instalar

Determine your setting material needs.  
Determinar la cantidad de material de fijación.

### 3 Grout Terminar

Choose your grout joint size and color.  
Elegir el tamaño y color de las juntas de cerámica.



Example over concrete  
Ejemplo sobre concreto



## Ceramic Tile Caulk Sanded & Non-Sanded

Use where horizontal and vertical surfaces meet.  
Use around tubs and sinks.



### Calafatear para Azulejos de Cerámica Con Arena y Sin Arena

High performance sealant for  
horizontal and vertical surfaces.  
Peg para juntas de cerámica.

Use around tubs and sinks.



This Product Contributes to  
Leadership in Energy and  
Environmental Design® certification.

Este producto contribuye a la certificación "Leadership in Energy and Environmental Design" (LEED).



**CUSTOM®**  
Building Products

800-273-8786

www.custombuildingproducts.com

LEED® is a Registered Trademark of U.S.G.B.C.

# POLYBLEND®

## Sanded Grout For Joints 1/8" to 1/2"

### Con Arena


Para juntas de cerámica de  
3 mm a 13 mm



## Non-Sanded Grout For Joints Up to 1/8"

### Sin Arena

Para juntas de cerámica de  
hasta 3 mm



Polyblend Grouts produce hard, durable  
grout joints and are easy to use, just  
add water and mix.

Los cerámicos Polyblend producen juntas de  
cerámica resistentes y duraderas y son fáciles de usar.  
Basta con agregar agua y mezclar.

## Coverage Cobertura

### How much grout do I need?

Grout joint size (mm)	Polyblend Sanded Grout 1/8" to 1/2" Joints	Polyblend Non-Sanded Grout Up to 1/8" Joints
JOINT SIZE (mm)	1/8" to 1/2"	Up to 1/8"
1/8" x 1/8" (3 mm x 3 mm)	1	1
1/8" x 1/4" (3 mm x 6 mm)	1	1
1/8" x 3/8" (3 mm x 10 mm)	1	1
1/8" x 1/2" (3 mm x 13 mm)	2	2
1/4" x 1/4" (6 mm x 6 mm)	2	2
1/4" x 3/8" (6 mm x 10 mm)	1	1

Coverage depends on joint size, depth, and mix. For best results, use a notched trowel to apply grout. Grout should be applied in a continuous motion. Grout should be applied in a continuous motion. Grout should be applied in a continuous motion.

### How many bags do I need?

can I grout?	Polyblend® sanded grout						56.7 lbs 25.3 kg
Minimum grout joint width	Joint size						
Minimum grout joint width	1/8" joint	1/4" joint	3/8" joint	1/2" joint	3/4" joint	1" joint	
1/8" x 1/8"	40	40	25	25	25	40	
1/8" x 1/4"	40	25	25	25	25	40	
1/8" x 3/8"	100	100	60	60	60	100	
1/8" x 1/2"	200	140	100	75	60	100	
1/4" x 1/4"	200	100	100	60	60	100	
1/4" x 3/8"	200	100	100	60	60	100	
1/4" x 1/2"	400	200	200	100	100	100	
3/8" x 3/8"	100	50	50	50	50	100	
3/8" x 1/2"	200	100	100	100	100	100	
1/2" x 1/2"	400	200	200	100	100	100	
1/2" x 3/8"	100	50	50	50	50	100	
1/2" x 1/4"	100	50	50	50	50	100	

Grout joint size (mm)	1/8"	1/4"	3/8"	1/2"	3/4"	1"
1/8" x 1/8" (3 mm x 3 mm)	40	40	25	25	25	40
1/8" x 1/4" (3 mm x 6 mm)	40	25	25	25	25	40
1/8" x 3/8" (3 mm x 10 mm)	100	100	60	60	60	100
1/8" x 1/2" (3 mm x 13 mm)	200	140	100	75	60	100
1/4" x 1/4" (6 mm x 6 mm)	200	100	100	60	60	100
1/4" x 3/8" (6 mm x 10 mm)	200	100	100	60	60	100
1/4" x 1/2" (6 mm x 13 mm)	400	200	200	100	100	100
3/8" x 3/8" (10 mm x 10 mm)	100	50	50	50	50	100
3/8" x 1/2" (10 mm x 13 mm)	200	100	100	100	100	100
1/2" x 1/2" (13 mm x 13 mm)	400	200	200	100	100	100
1/2" x 3/8" (13 mm x 10 mm)	100	50	50	50	50	100
1/2" x 1/4" (13 mm x 6 mm)	100	50	50	50	50	100